



Rogers Fencing Q40 Specification

Double Leaf Gate

Manufacturer And Reference:	Rogers Fencing Supplies Ltd (02879627264) Double Leaf Gate. Galvanised and Polyester Powder Coated by RFS approved applicator to BS6497
Drawing Reference	RFS/PS/DB/2.4
Height	2.4m
Width	1500mm-6000mm clear opening
Finish	Galvanized to BS EN ISO 1461:1999 and polyester powder coated to BS6497 by an approved applicator RAL:6005
Frame	60x40mm having panels securely welded to gate frame.
Gate Posts	150x150x6mm RHS set in concrete bases 750x750x1000mm deep completely filled with 20N concrete
Fittings	RFS 24mm adjustable hinges, drop bolts, centre box, rear ground sockets, Anti Climb latch incorporating slip bolt for client's padlock.
Post Bases	750x750x1000mm deep completely filled with 20N concrete.
Installation	Set out and erect gate as shown on drawings, with posts set rigid, plumb and to specified depth, or greater where necessary to ensure adequate support. With correct fastenings and all components securely fixed.

Rogers Fencing Supplies Ltd, Rogers Business Park, 76 Derrynoid Road, Draperstown BT45 7DW

Tel: 028 796 27264 E: sales@rogersfencing.com W: www.rogersfencing.com

Company Reg: NI607823