



## **Rogers Fencing Supplies Ltd Q40 Specification**

### **Palisade Fencing System**

Manufacturer and Reference	Rogers Fencing Supplies Ltd (02879627264) Palisade G-P Spec
Drawing Reference:	RFS/PALIS/1
Height	2.40
Rails	45 x 45 x 6mm RSA, 2 no fish plated to posts.
Pales	D section pales having Type A Triple Point Splayed 3.0mm thick, fixed to rails at 152mm centres
Finish	Hot dipped Galvanised to BS EN ISO 1461: 1999
Posts	100 x 55 IPE intermediate fence posts, set in concrete bases 450x450x750mm deep, completely filled with 20N concrete at centres no greater than 2750mm.
Fixings	Rails to be fixed to posts using fish plates and M12 x 40 Permacone bolts and saddle head nuts. Pales to be fixed to rails using M8 x 40 Saddle head and permacone bolted connections.
Installation	Set out and erect fencing in straight lines or smoothly flowing curves as shown on drawings, with tops of posts following profile of the ground, with posts set rigid, plumb and to specified depth, or greater where necessary to ensure adequate support. With correct fastenings and all components securely fixed.

**Rogers Fencing Supplies Ltd, Rogers Business Park, 76 Derrynoid Road, Draperstown BT45 7DW**

**Tel: 028 796 27264 E: [sales@rogersfencing.com](mailto:sales@rogersfencing.com) W: [www.rogersfencing.com](http://www.rogersfencing.com)**