



## Rogers Fencing Q40 Specification

### **HEAVY DUTY CLASSIC MESH FENCING SYSTEM**

Manufacturer and Reference	Rogers Fencing Supplies Ltd (02879627264) 2400mm high Heavy Duty Classic Mesh Fencing System. Galvanised and Polyester Powder Coated by RFS approved applicator to BS6497
Drawing Reference:	RFS/HDCM/2400/01
Height	2.40 m
Mesh	Rogers Fencing Supplies Heavy Duty Classic Mesh Panel. Having a Wire mesh aperture of 200 x 25mm for the overall panel height of 2.4m. Incorporating 6mm horizontal wires, and 5mm vertical wires with 4 no. folded beams for increased rigidity. 30mm protruding wires
Finish	Galvanised to BS EN ISO 1461:1999 and polyester powder coated to BS6497 by an approved RFS applicator. Such as MSF (02827657075) Colour RAL: MOSS GREEN 6005
Posts	60x60x3 mm RHS. Posts set in concrete bases 450x450x750mm deep completely filled with 20N concrete at centres no greater than 2460mm. Posts to be fitted with M8 threaded inserts every 400mm tensioned only by hydraulic tool.
Fixings	Panels to be secured to posts using 25 x 5mm slotted clamp bar with M8 safe security anti-vandal stainless steel bolts
Installation	Set out and erect fencing in straight lines or smoothly flowing curves as shown on drawings, with tops of posts following profile of the ground, with posts set rigid, plumb and to specified depth, or greater where necessary to ensure adequate support. With correct fastenings and all components securely fixed

**Rogers Fencing Supplies Ltd, Rogers Business Park, 76 Derrynoid Road, Draperstown BT45 7DW**

**Tel: 028 796 27264 E: [sales@rogersfencing.com](mailto:sales@rogersfencing.com) W: [www.rogersfencing.com](http://www.rogersfencing.com)**